

Code: BL 7002



LED ARMATÜR Led Armature

- Korozyona dayanıklı alüminyum enjeksiyon armatür.
- 220-240V/ 50-60 Hz enerji giriřli
- Akıllı soğutma tasarımı
- 3000K ile 6500K arası renk sıcaklığı seçenekleri mevcuttur
- Led trafosu kolayca deęiřtirilebilir
- Dıř vidalar paslanmaz çelik
- Konsol iç kapı Ø42-Ø76mm arası uyumludur.

- Corrosion resistant die-cast aluminum body.
- Mains voltage: 220-240V/50-60Hz.
- Clever thermal desing
- Led colour temperatures optionally from 3000K to led 6500K
- Replaceable driver unit and control gear
- All external scrwes are in stainless steel.
- Pole-top installation on poles with ending part from Ø42 to Ø76 mm.



□ White / Beyaz
■ Gray / Gri
■ Black / Siyah



KOD Code	LED TİPİ Led Type	POWER Güç	LUMEN Lumen	KELVİN	BEAM AGLE Iřık Açısı
BL7002.30	Power Led	30W	3.000 lm	3000K	150° Asimetrik
BL7002.30	Power Led	30W	3.300 lm	4000K	150° Asimetrik
BL7002.30	Power Led	30W	3.450 lm	6500K	150° Asimetrik
BL7002.45	Power Led	45W	4.500 lm	3000K	150° Asimetrik
BL7002.45	Power Led	45W	4.950 lm	4000K	150° Asimetrik
BL7002.45	Power Led	45W	5.175 lm	6500K	150° Asimetrik
BL7002.60	Power Led	60W	6.000 lm	3000K	150° Asimetrik
BL7002.60	Power Led	60W	6.600 lm	4000K	150° Asimetrik
BL7002.60	Power Led	60W	6.900 lm	6500K	150° Asimetrik
BL7002.70	Power Led	70W	7.000 lm	3000K	150° Asimetrik
BL7002.70	Power Led	70W	7.700 lm	4000K	150° Asimetrik
BL7002.70	Power Led	70W	8.050 lm	6500K	150° Asimetrik
BL7002.100	Power Led	100W	10.000 lm	3000K	150° Asimetrik
BL7002.100	Power Led	100W	11.000 lm	4000K	150° Asimetrik
BL7002.100	Power Led	100W	11.500 lm	6500K	150° Asimetrik

