



Technical information


Order code	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
BL 9235	300	45000	150
BL 9235	400	60000	150
BL 9235	500	75000	150

Order code	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
BL 9235	600	90000	150
BL 9235	700	105000	150
BL 9235	800	120000	150
BL 9235	900	135000	150
BL 9235	1000	150000	150

Order code	Power (W)	Luminaire output flux (lm)	Luminaire efficacy (lm/W)
BL 9235	1100	165000	150
BL 9235	1200	180000	150
BL 9235	1300	195000	150
BL 9235	1400	210000	150
BL 9235	1500	225000	150

Parameter	Technical data	Parameter	Technical data
Lifetime	Up to 100,000hrs LM70,Ta 25°C	Driver isolation	Class I
Wattags	300~1500W	Control dimming	DAU / 1-10V / Timing / PWM
Light efficacy	Up to 171lm/W	Operating temperature	-35°C~50°C / 10% ~ 95% (humidity)
CRI	≥ 70 or ≥ 80	Body parts material	ADC12 (standard)
Color temperature	3000K, 4000K, 5000K, 6500K	Optic	PC (standard)
Operation voltage	AC 90-305V or AC 220-240V	Screen	Flat tempered glass 5mm thickness
Frequency	50 / 60Hz	Gasket	Silicone
Power factor	≥0.95 cos	Color stability	3 or 5 MacAdam steps

Packing Information



Carton Size(L*W*H)	QTY/Carton	N.W.(kg)	G.W.(kg)
685*435*250mm	1	17	18
805*765*265mm	1	30	33
1190*800*340mm	1	48	52

Optics Available



FD620



FD630



FD660



FD690



FD6P50



FD6P60

